

PROV

Providence® Medium



DESIGNER
SSL SERIES
FEATURING
MICROEMITTER™
TECHNOLOGY



FEATURES


- Part of AAL's Designer SSL Series
- Features highly efficient, exclusive MicroEmitter™ technology
- Features exclusive wiHUBB technology
 - Wireless control system for use with 0-10VDC interface for full range dimming capabilities
 - Programmable autonomous operation
- Field replaceable LED EmitterDeck™ upgrade kits for PROV-H - See page 864 for details.
- DLC approved (Type 3 and 5, 5100K)
- Features exclusive LifeShield™ Protection System
- 0-10v dimming capabilities
- Slips over a 4" tenon for arm or pole mounting
- EISA compliant
- IP55 rated
- Powder coat finish in 13 standard colors with a polymer primer sealer

ORDERING INFORMATION

PROV - [] - [] - []

MODEL	
LED	
60 light emitting diode array (72 total luminaire input watts). 120 thru 277 volt.	
Warm White (3500K)	
PROV-T2-60LED-WW	IES Type 2 distribution
PROV-T3-60LED-WW	IES Type 3 distribution
PROV-T4-60LED-WW	IES Type 4 distribution
PROV-T5-60LED-WW	IES Type 5 distribution
Bright White (5100K)	
PROV-T2-60LED-BW	IES Type 2 distribution
PROV-T3-60LED-BW	IES Type 3 distribution
PROV-T4-60LED-BW	IES Type 4 distribution
PROV-T5-60LED-BW	IES Type 5 distribution
Comes complete with LEDs and driver. Class 1, 350mA drive current.	
HID/CFL	
PROV-H2	Type 2 horizontal reflector, flat tempered clear glass lens
PROV-H3	Type 3 horizontal reflector, flat tempered clear glass lens
PROV-H4	Type 4 horizontal reflector, flat tempered clear glass lens
PROV-H5	Type 5 horizontal reflector, flat tempered clear glass lens
PROV-V3	Type 3 vertical reflector, tempered clear sag glass lens
PROV-V5	Type 5 vertical reflector, tempered clear sag glass lens
PROV-INDA	Asymmetric indirect reflective optical system, metal halide lamps only.
PROV-INDS	Symmetric indirect reflective optical system, metal halide lamps only.
Ballast not included	

DIMENSIONS



WEIGHT: 29 lbs EPA: 0.96

LAMP/BALLAST	
50MH	50 watt metal halide 120/208/240/277 volt ballast. Use medium base, ED-17 lamp.
50MHEB	50 watt electronic metal halide 120 thru 277 volt ballast. Use medium base, ED-17 lamp.
70MH	70 watt metal halide 120/208/240/277 volt ballast. Use medium base, ED-17 lamp.
70MHEB	70 watt electronic metal halide 120 thru 277 ballast. Use medium base, ED-17 lamp.
70MHT6	70 watt metal halide 120/277/347 volt ballast. Use G12 base, T-6 ceramic lamp.
70MHT6EB	70 watt electronic metal halide 120 thru 277 volt ballast. Use G12 base, T-6 ceramic lamp.
100MH	100 watt metal halide 120/208/240/277 volt ballast. Use medium base, ED-17 lamp.
150PSMH	Pulse start 150 watt metal halide 120/208/240/277 volt ballast. Use medium base, ED-17 lamp.
150PSMHT6	Pulse start 150 watt metal halide 120/208/240/277 volt ballast. Use G12 base, T-6 ceramic lamp.
150MHEB	150 watt electronic metal halide 120 or 277 volt ballast. Use medium base, ED-17 lamp.
150MHT6EB	150 watt electronic metal halide 120 or 277 volt ballast. Use G12 base, T-6 ceramic lamp.
175PSMH	Pulse start 175 watt metal halide 120/208/240/277 volt ballast. Use medium base, ED-17 lamp. Vertical reflector only.
70HPS	70 watt high pressure sodium 120/208/240/277 volt ballast. Use medium base, ED-17 lamp.
100HPS	100 watt high pressure sodium 120/208/240/277 volt ballast. Use medium base, ED-17 lamp.
150HPS	150 watt high pressure sodium 120/208/240/277 volt ballast. Use medium base, ED-17 lamp.
CF	Compact fluorescent, electronic 120 thru 277 volt ballast. Use GX24base, 26,32 or 42 watt lamp (direct only). -18°C minimum starting temp.

All ballasts are factory wired for 277 volts unless specified. Lamps not included. All applicable ballasts are EISA compliant

OPTIONS	
WIH-IM	In fixture wireless control system. For LED only.
SPK	Decorative cast aluminum spikes on the top and bottom of the four vertical struts.
PFN	Cast aluminum finial painted a brass color.
BPS	Cast aluminum struts painted a brass color - spikes also painted brass if option SPK chosen
HSS	House side shield. Not available with LED.
LDL	Lightly diffused lens. For horizontal reflector models. Not available with LED.
QL	Socket for T-4 mini-can lamp, field wired to a separate circuit. (Lamp wattage not to exceed ballast wattage). Horizontal reflectors only. Not available with LED.
QRS	Restrike controller and T-4 mini-can socket. Not required with electronic ballast. (Lamp wattage not to exceed ballast wattage). Horizontal reflectors only. Not available with LED.

COLORS	
AWT	Arctic White
BLK	Black
MTB	Matte Black
DGN	Dark Green
DBZ	Dark Bronze
WRZ	Weathered Bronze
BRM	Metallic Bronze
VBL	Verde Blue
CRT	Corten
MAL	Matte Aluminum
MDG	Medium Grey
ATG	Antique Green
LGY	Light Grey
RAL/PREMIUM COLOR	Provide a RAL 4 digit color number
CUSTOM COLOR	Please provide a color chip for matching

Please visit www.aal.net for mounting options.