

LED Upgrade Kits

Designer SSL Series – Traditional Luminaires

PERIOD



NEW

**DESIGNER
SSL**
SERIES
FEATURING
MICROEMITTER™
TECHNOLOGY

FEATURES

- Upgrade existing AAL HID luminaires to LED in the field
- Available for all Designer SSL Series luminaires
- Easy 10-minute field conversion
- No need to replace entire luminaire
- Upgrade LEDs as technology advances
- Individual MicroEmitters™ are field replaceable
- Available in warm white (3500K) and bright white (5100K) color temperatures
- IES Types 2, 3, 4 or 5 available
- Features exclusive LifeShield™ Protection System
- 0-10V dimming capabilities

ORDERING INFORMATION

UPGRADE KITS

MODEL	
Providence® Medium Scale	
PROV-H	
RK3509	60 LED (72 watts), IES Type 2 distribution, warm white (3500K)
RK3510	60 LED (72 watts), IES Type 3 distribution, warm white (3500K)
RK3511	60 LED (72 watts), IES Type 4 distribution, warm white (3500K)
RK3512	60 LED (72 watts), IES Type 5 distribution, warm white (3500K)
RK5109	60 LED (72 watts), IES Type 2 distribution, bright white (5100K)
RK5110	60 LED (72 watts), IES Type 3 distribution, bright white (5100K)
RK5111	60 LED (72 watts), IES Type 4 distribution, bright white (5100K)
RK5112	60 LED (72 watts), IES Type 5 distribution, bright white (5100K)
Providence® Large Scale	
PROL-H	
RK3525	108 LED (124 watts), IES Type 2 distribution, warm white (3500K)
RK3526	108 LED (124 watts), IES Type 3 distribution, warm white (3500K)
RK3527	108 LED (124 watts), IES Type 4 distribution, warm white (3500K)
RK3528	108 LED (124 watts), IES Type 5 distribution, warm white (3500K)
RK5125	108 LED (124 watts), IES Type 2 distribution, bright white (5100K)
RK5126	108 LED (124 watts), IES Type 3 distribution, bright white (5100K)
RK5127	108 LED (124 watts), IES Type 4 distribution, bright white (5100K)
RK5128	108 LED (124 watts), IES Type 5 distribution, bright white (5100K)
Class 1, 120 thru 277 volt. 350mA drive current.	

MODEL	
Promenade™	
PRMN	
RK3513	60 LED (73 watts), IES Type 2 distribution, warm white (3500K)
RK3514	60 LED (73 watts), IES Type 3 distribution, warm white (3500K)
RK3515	60 LED (73 watts), IES Type 4 distribution, warm white (3500K)
RK3516	60 LED (73 watts), IES Type 5 distribution, warm white (3500K)
RK5113	60 LED (73 watts), IES Type 2 distribution, bright white (5100K)
RK5114	60 LED (73 watts), IES Type 3 distribution, bright white (5100K)
RK5115	60 LED (73 watts), IES Type 4 distribution, bright white (5100K)
RK5116	60 LED (73 watts), IES Type 5 distribution, bright white (5100K)
PRMS	
RK3517	60 LED (73 watts), IES Type 2 distribution, warm white (3500K)
RK3518	60 LED (73 watts), IES Type 3 distribution, warm white (3500K)
RK3519	60 LED (73 watts), IES Type 4 distribution, warm white (3500K)
RK3520	60 LED (73 watts), IES Type 5 distribution, warm white (3500K)
RK5117	60 LED (73 watts), IES Type 2 distribution, bright white (5100K)
RK5118	60 LED (73 watts), IES Type 3 distribution, bright white (5100K)
RK5119	60 LED (73 watts), IES Type 4 distribution, bright white (5100K)
RK5120	60 LED (73 watts), IES Type 5 distribution, bright white (5100K)
PRMD	
RK3521	60 LED (73 watts), IES Type 2 distribution, warm white (3500K)
RK3522	60 LED (73 watts), IES Type 3 distribution, warm white (3500K)
RK3523	60 LED (73 watts), IES Type 4 distribution, warm white (3500K)
RK3524	60 LED (73 watts), IES Type 5 distribution, warm white (3500K)
RK5121	60 LED (73 watts), IES Type 2 distribution, bright white (5100K)
RK5122	60 LED (73 watts), IES Type 3 distribution, bright white (5100K)
RK5123	60 LED (73 watts), IES Type 4 distribution, bright white (5100K)
RK5124	60 LED (73 watts), IES Type 5 distribution, bright white (5100K)
Class 1, 120 thru 277 volt. 350mA drive current.	

Upgrade kits also available for contemporary Designer SSL Series luminaires. Please see contemporary section, page 880.