

CodeLinkSM



Scan code to download Federal Style bollards (FCB1/FCB3) spec sheet



Scan code to download Colonial Style bollard (FCB5) spec sheet

FairOaksTM

Bollard Collection

- ▶ Classic Styling
- ▶ Rugged Design

ARCHITECTURAL AREA LIGHTING



Fair Oaks™ Bollards

Classic styling

Federal styling coordinates perfectly with AAL luminaires and poles

Versatile

Available as a lit or unlit bollard

Rugged Design

Made of cast aluminum for corrosion resistance

Energy Efficient

Utilizes energy efficient sources



FCB1



BOLLARD

FCB1-C	Clear acrylic lens
FCB1-F	Frosted acrylic lens
FCB1-PC	Clear polycarbonate lens
FCB1-PF	Frosted polycarbonate lens
FCB1-UN	Unlit decorative bollard

LAMP/BALLAST

50MH	50 watt metal halide 120/208/240/277 volt ballast. Use medium base, ED-17 lamp.
50MHEB	50 watt electronic metal halide 120 thru 277 volt ballast. Use medium base, ED-17 lamp.
70MH	70 watt metal halide 120/208/240/277 volt ballast. Use medium base, ED-17 lamp.
70MHT6	70 watt metal halide 120/277/347 volt ballast. Use G12 base, T-6 ceramic lamp.
70MHEB	70 watt electronic metal halide 120 thru 277 volt ballast. Use medium base, ED-17 lamp.
70MHT6EB	70 watt electronic metal halide 120 thru 277 volt ballast. Use G12 base, T-6 ceramic lamp.
50HPS	50 watt high pressure sodium 120/277 volt ballast. Use medium base, ED-17 lamp.
70HPS	70 watt high pressure sodium 120/208/240/277 volt ballast. Use medium base, ED-17 lamp.
CF	Compact fluorescent electronic 120 thru 277 volt ballast. -18° min. start temp. Use GX24q 4-pin 26, 32 or 42 watt lamp.

All ballasts are factory wired for 277 volts, unless specified. Lamps not included. All applicable ballasts are EISA compliant.

COLOR

All standard AAL colors available for grill. For RAL and custom colors, please submit a 4-digit RAL number or color chip for custom colors.

OPTIONS

90S	House side shield, 90°
180S	House side shield, 180°
FS1	Single weatherproof fuse holder. Fuse by others.
FS2	Double weatherproof fuse holder. Fuse by others.
GFI	Ground fault interrupter
CE1	Chain eyes, single
CE2	Chain eyes, double

Ordering Information Example

BOLLARD

FCB1-F

LAMP/BALLAST

70MH

COLOR

WRZ

OPTIONS

90S

Refer to AAL's Fair Oaks Bollard brochure for photometry and complete specification and ordering details.



16555 East Gale Ave.
City of Industry | CA 91745
T 626.968.5666 | F 626.369.2695
www.aal.net



Fair Oaks™ Bollards

Classic styling

Federal styling coordinates perfectly with AAL luminaires and poles

Versatile

Available as a lit or unlit bollard

Rugged Design

Made of cast aluminum for corrosion resistance

Energy Efficient

Utilizes energy efficient sources



FCB3



BOLLARD

FCB3-C	Clear acrylic lens
FCB3-F	Frosted acrylic lens
FCB3-PC	Clear polycarbonate lens
FCB3-PF	Frosted polycarbonate lens
FCB3-UN	Unlit decorative bollard

LAMP/BALLAST

50MH	50 watt metal halide 120/208/240/277 volt ballast. Use medium base, ED-17 lamp.
50MHEB	50 watt electronic metal halide 120 thru 277 volt ballast. Use medium base, ED-17 lamp.
70MH	70 watt metal halide 120/208/240/277 volt ballast. Use medium base, ED-17 lamp.
70MHT6	70 watt metal halide 120/277/347 volt ballast. Use G12 base, T-6 ceramic lamp.
70MHEB	70 watt electronic metal halide 120 thru 277 volt ballast. Use medium base, ED-17 lamp.
70MHT6EB	70 watt electronic metal halide 120 thru 277 volt ballast. Use G12 base, T-6 ceramic lamp.
50HPS	50 watt high pressure sodium 120/277 volt ballast. Use medium base, ED-17 lamp.
70HPS	70 watt high pressure sodium 120/208/240/277 volt ballast. Use medium base, ED-17 lamp.
CF	Compact fluorescent electronic 120 thru 277 volt ballast. Use GX24q 4-pin 26, 32 or 42 watt lamp. -18° min. start temp. Specify wattage.

All ballasts are factory wired for 277 volts, unless specified. Lamps not included. All applicable ballasts are EISA compliant.

COLOR

All standard AAL colors available for grill. For RAL and custom colors, please submit a 4-digit RAL number or color chip for custom colors.

OPTIONS

90S	House side shield, 90°
180S	House side shield, 180°
FS1	Single weatherproof fuse holder. Fuse by others.
FS2	Double weatherproof fuse holder. Fuse by others.
GFI	Ground fault interrupter
CE1	Chain eyes, single
CE2	Chain eyes, double

Ordering Information Example

BOLLARD
FCB3-F

LAMP/BALLAST
70MH

COLOR
CRT

OPTIONS
90S

Refer to AAL's Fair Oaks Bollard brochure for photometry and complete specification and ordering details.



16555 East Gale Ave.
City of Industry | CA 91745
T 626.968.5666 | F 626.369.2695
www.aal.net



Fair Oaks™ Bollards

Classic styling

Colonial styling coordinates perfectly with AAL luminaires and poles

Versatile

Available with a wide variety of optical systems

Rugged Design

Made of cast aluminum for corrosion resistance

Energy Efficient

Utilizes energy efficient sources including LED



FCB5



COLONIAL BOLLARD

FCB5-C	Clear acrylic lens
FCB5-F	Frosted acrylic lens
FCB5-PC	Clear polycarbonate lens
FCB5-PF	Frosted polycarbonate lens
FCB5-GR3	Clear acrylic lens, glass refractor. Type 3 distribution.
FCB5-GR5	Clear acrylic lens, glass refractor. Type 5 distribution.
FCB5-ILV	Clear acrylic lens, internal louvers. Type 5 distribution.
FCB5-ELV	Clear acrylic lens, external louvers. Type 5 distribution.
FCB4-LED	Clear acrylic lens, indirect LED. Type 5 distribution.
FCB5-UN	Unlit decorative bollard

LAMP/BALLAST

50MH	50 watt metal halide 120/208/240/277 volt ballast. Use medium base, ED-17 lamp.
50MHEB	50 watt electronic metal halide 120 thru 277 volt ballast. Use medium base, ED-17 lamp.
70MH	70 watt metal halide 120/208/240/277 volt ballast. Use medium base, ED-17 lamp.
70MHT6	70 watt metal halide 120/277/347 volt ballast. Use G12 base, T-6 ceramic lamp.
70MHEB	70 watt electronic metal halide 120 thru 277 volt ballast. Use medium base, ED-17 lamp.
70MHT6EB	70 watt electronic metal halide 120 thru 277 volt ballast. Use G12 base, T-6 ceramic lamp.
50HPS	50 watt high pressure sodium 120/277 volt ballast. Use medium base, ED-17 lamp.
70HPS	70 watt high pressure sodium 120/208/240/277 volt ballast. Use medium base, ED-17 lamp.
CF	Compact fluorescent electronic 120 thru 277 volt ballast. -18° min. start temp. Use GX24q 4-pin base, 26, 32 or 42 watt lamp. Specify wattage.
24LED-WW	24 light emitting diode array (53 watt). 120 thru 277 volt. Warm white (3500K). Available with LED bollard only. Drive current 700mA.
24LED-BW	24 light emitting diode array (53 watt). 120 thru 277 volt. Bright white (5100K). Available with LED bollard only. Drive current 700mA.

All ballasts are factory wired for 277 volts, unless specified. Lamps not included. All applicable ballasts are EISA compliant.

COLOR

All standard AAL colors available for grill. For RAL and custom colors, please submit a 4-digit RAL number or color chip for custom colors.

OPTIONS

90S	House side shield, 90°
180S	House side shield, 180°
FS1	Single weatherproof fuse holder. Fuse by others.
FS2	Double weatherproof fuse holder. Fuse by others.
GFI	Ground fault interrupter
CE1	Chain eyes, single
CE2	Chain eyes, double
UB6	6" ball finial. Only available with unlit (UN) bollard

Ordering Information Example

BOLLARD
FCB5-F

LAMP/BALLAST
70MHEB

COLOR
BLK

OPTIONS
180S

Refer to AAL's Fair Oaks brochure for photometry and complete specification and ordering details.



16555 East Gale Ave.
City of Industry | CA 91745
T 626.968.5666 | F 626.369.2695
www.aal.net

