

# PROMENADE™

# LED

PRMD



CodeLink<sup>SM</sup>

Scan code  
to download  
**PRMD-LED**  
Spec Sheet



- Superior Performance
- Elegant Styling

DESIGNER  
**SSL** SERIES  
FEATURING  
MICROEMITTER™  
TECHNOLOGY

ARCHITECTURAL AREA LIGHTING



# Promenade™ LED – PRMD

NEW LED MODELS



## Traditional Styling

Traditional look with modern performance

## MicroEmitter™ LED Technology

Powerful, uniform illumination with low glare

## Canted MicroEmitter Design

Precisely aims each diode for maximum reach and uniformity

## Upgradeable

Upgrade the LED EmitterDeck™ as technology advances or retrofit existing HID installations

## LifeShield™ Protection System

Preserves diode life in extreme ambient conditions

## Dimming Control

0 - 10v dimming capabilities



PRMD with optional FTG



## ORDERING INFORMATION

### LUMINAIRE/LED CONFIGURATION

#### PRMD-T2-60LED-WW

IES Type 2 distribution. 60 light emitting diode array (73 watts). Class 1, 120 thru 277 volt. Warm white (3500K).

#### PRMD-T3-60LED-WW

IES Type 3 distribution. 60 light emitting diode array (73 watts). Class 1, 120 thru 277 volt. Warm white (3500K).

#### PRMD-T4-60LED-WW

IES Type 4 distribution. 60 light emitting diode array (73 watts). Class 1, 120 thru 277 volt. Warm white (3500K).

#### PRMD-T5-60LED-WW

IES Type 5 distribution. 60 light emitting diode array (73 watts). Class 1, 120 thru 277 volt. Warm white (3500K).

350mA drive current.

#### PRMD-T2-60LED-BW

IES Type 2 distribution. 60 light emitting diode array (73 watts). Class 1, 120 thru 277 volt. Bright white (5100K).

#### PRMD-T3-60LED-BW

IES Type 3 distribution. 60 light emitting diode array (73 watts). Class 1, 120 thru 277 volt. Bright white (5100K).

#### PRMD-T4-60LED-BW

IES Type 4 distribution. 60 light emitting diode array (73 watts). Class 1, 120 thru 277 volt. Bright white (5100K).

#### PRMD-T5-60LED-BW

IES Type 5 distribution. 60 light emitting diode array (73 watts). Class 1, 120 thru 277 volt. Bright white (5100K).



### UPGRADE KIT

A field replaceable upgrade kit is available for existing PRMD HID/CFL models. The kit comes complete with drivers and 20 LED microEmitters (60 diodes/73 watts). Please contact your AAL representative for complete details.

### COLOR

All 13 standard AAL colors available. For RAL, please submit a 4-digit RAL number or color chip for custom colors.

### OPTIONS

MAT	Cast adapter to side mount to mast arm	FTG	Flat glass lens
VSR	30" diameter visor	LDL	Lightly diffused lens
		HSS	House side shield

### MOUNTING

Standard is arm mount in down position. Please visit [www.aal.net](http://www.aal.net) for a complete selection of decorative arms.

## Ordering Information Example

LUMINAIRE  
PRMD-T2-60LED-WW

COLOR  
BLK

OPTIONS  
FTG

MOUNTING  
See Brochure

Refer to AAL's Promenade brochure for photometry and complete specification and ordering details.

**DESIGNER**  
**SSL** SERIES  
FEATURING  
**MICROEMITTER™**  
TECHNOLOGY

PATENTS PENDING



HUBBELL LIGHTING, INC.

16555 East Gale Ave.  
City of Industry | CA 91745  
T 626.968.5666 | F 626.369.2695  
[www.aal.net](http://www.aal.net)

