

Small Scale - Indirect

Updated: 01/2010



- Concealed light source for smooth, glare free illumination
- Cutoff option
- Symmetric or asymmetric distribution
- Post-top, wall mount arm, or pole mount arm options
- Tool-less access with captive fastener.
- Stainless steel struts
- EISA compliant
- IP65 rated
- Powder coat finish in 13 standard colors with a polymer primer sealer



Architectural Area Lighting

16555 East Gale Ave. | City of Industry | CA 91745
P 626.968.5666 | F 626.369.2695 | www.aal.net
Design patents, Copyright © 2010 Rev 01/2010

Fixture	Lens Element	Lamp/Ballast	Hood Finish	Color	Options	Mounting
1	2	3	4	5	6	7

1. FIXTURE

SP2-IND Spectra Small Scale-Indirect _____

Dimensions:


23.5 in/597 mm HT x 23.9 in/610 mm DIA

WT: 35 lbs

EPA: 1.43 IP: 65

Slips over a 3 in/75 mm O.D. pole

Note: Spectra Indirect ships with Straight hood as standard.



2. LENS ELEMENT

-3 Type 3 light distribution _____

-5 Type 5 light distribution _____

3. LAMP/BALLAST

CF 120 thru 277 electronic ballast for use with 4 pin, 32 or 42 watt T-4 compact fluorescent lamp. _____

50MH 50 watt metal halide 120/277 volt ballast. Use medium base, ED-17 lamp. _____

50MHEB 50 watt electronic metal halide 120 thru 277 volt ballast. Use medium base, ED-17 lamp. _____

70MH 70 watt metal halide 120/208/240/277 volt ballast. Use medium base, ED-17 lamp. _____

70MHEB 70 watt electronic metal halide 120 thru 277 volt ballast. Use medium base, ED-17 lamp. _____

70MHT6 70 watt metal halide 120/277 volt ballast. Use G12 base, T-6 ceramic lamp. _____

70MHT6EB 70 watt electronic metal halide 120 thru 277 volt ballast. Use G12 base, T-6 ceramic lamp. _____

100MH 100 watt metal halide 120/208/240/277 volt ballast. Use medium base, ED-17 lamp. _____

100MHEB 100 watt electronic metal halide 120 thru 277 volt ballast. Use medium base, ED-17 lamp. _____

50HPS 50 watt high pressure sodium 120/277 volt ballast. Use medium base, ED-17 lamp. _____

70HPS 70 watt high pressure sodium 120/208/240/277 volt ballast. Use medium base, ED-17 lamp. _____

100HPS 100 watt high pressure sodium 120/208/240/277 volt ballast. Use medium base, ED-17 lamp. _____

All fixtures prewired for 277 volts, unless specified. Lamps not included.

All applicable ballasts are EISA compliant.

SOLD TO

PO #

JOB NAME

Approvals

Architectural Area Lighting

16555 East Gale Ave. | City of Industry | CA 91745
 P 626.968.5666 | F 626.369.2695 | www.aal.net
 Design patents, Copyright © 2010 Rev 01/2010

Fixture	Lens Element	Lamp/Ballast	Hood Finish	Color	Options	Mounting
1	2	3	4	5	6	7

4. HOOD FINISH-OPTIONAL

- STS Stainless steel
- COP Natural copper

Indirect model hoods have the underside finished in high reflectance white.

5. COLOR

- AWT Arctic White
- BLK Black
- MTB Matte Black
- DGN Dark Green
- DBZ Dark Bronze
- WRZ Weathered Bronze
- BRM Metallic Bronze
- VBL Verde Blue
- CRT Corten
- MAL Matte Aluminum
- MDG Medium Grey
- ATG Antique Green
- LGY Light Grey
- RAL/PREMIUM COLOR Provide a RAL 4 digit color number
- CUSTOM COLOR Please provide a color chip for matching

6. OPTIONS

- 347 120/227/347 volt ballast
- ULS Upper lens shield above the hood. Provides cutoff classification.
- AD4 Adapter for SP2, slips over a 4 in/100 mm O.D. pole.

7. MOUNTING

- AWM2 Wall mounted arm for SP2. WT: 5 lbs EPA: 0.11
- SAP2 Arm mount for SP2. Designed to slip over a 4 in/100 mm pole. WT: 9 lbs EPA: .63
- TAP2 Twin arm mount for SP2. Designed to slip over a 4 in/100 mm pole. WT: 12 lbs EPA: .83

SOLD TO

PO #


JOB NAME

Approvals

Architectural Area Lighting

16555 East Gale Ave. | City of Industry | CA 91745
P 626.968.5666 | F 626.369.2695 | www.aal.net
Design patents, Copyright © 2010 Rev 01/2010

Specifications



Dimensions:

23.5 in/597 mm HT x 23.9 in/610 mm DIA

WT: 35 lbs

EPA: 1.43 IP: 65

HOUSING

The fixture housing is all cast aluminum, A356 alloy, free of any porosity, foreign materials, or cosmetic fillers. The ballast is mounted internally and accessed by loosening two captive bolts and lifting off the top of the fixture. The top cover is hinged and secured with one captive tool-less fastener for relamping. The top is sealed with a molded silicone gasket. The upper reflector cone is matte finished anodized aluminum. All lenses are molded, seamless high impact lighting grade acrylic. The lens is sealed to the housing with a molded silicone gasket on the top and bottom. The vertical struts are 316 stainless steel tubing. All internal and external hardware is stainless steel. All female threads on the aluminum parts are cast-in-place brass inserts to ensure no thread seizure.

The fixture shall slip over a 3 in/75mm round post top and secured with six stainless steel set screws.

The shade is spun from 6061 T-6 aluminum, 316 stainless steel or 110 copper. The shade has a beaded edge for added strength. For indirect models, the underside of the painted, copper, and stainless steel shades are finished in a high reflectance white powder coating.

ELECTRICAL

The ballast is integral to the fixture, mounted on a prewired module with a quick disconnect plug. The ballast module has two keyhole slots and is removable by loosening two screws. Sockets is pulse rated porcelain. HID ballasts are high power factor, rated for -30° C starting. The compact fluorescent ballast shall be electronic for use with 4 pin lamps (GX24q-4 socket) rated for -18° C starting temperature. Ballasts are multitap, wired at the factory for 277 volts, unless specified.

FINISH

Fixture finish consists of a five stage pretreatment regimen with a polymer primer sealer, oven dry off and top coated with a thermoset super TGIC polyester powder coat finish. The finish shall meet the AAMA 605.2 performance specification which includes passing a 3000 hour salt spray test for corrosion resistance.

EISA COMPLIANCE

AAL is committed to complying with U.S. EISA requirements. All applicable products manufactured for sale in the United States after January 1, 2009, will meet EISA requirements.

CERTIFICATION

The fixture is listed with ETL for outdoor, wet location use, UL1598 and Canadian CSA Std. C22.2 no.9. IP=65

WARRANTY

Fixture is warranted for three years. Ballast components carry the ballast manufacturer's limited warranty. Any unauthorized return, repair, replacement or modification of the Product(s) shall void this warranty. This warranty applies only to the use of the Product(s) as intended by AAL and does not cover any misapplication or misuse of said Product(s), or installation in hazardous or corrosive environments. Contact AAL for complete warranty language, exceptions, and limitations.

Architectural Area Lighting

16555 East Gale Ave. | City of Industry | CA 91745
P 626.968.5666 | F 626.369.2695 | www.aal.net
Design patents, Copyright © 2010 Rev 01/2010