










LED Product Offerings

FAMILY	LUMINAIRE CODE*	LED CONFIGURATION*	WATTAGE CONSUMPTION	LUMEN OUTPUT	LPW	CCT
Parkway Square™	PKWM 	T3-60LED-BW	73 watts	3144	43	5100K
		T5-60LED-BW	72 watts	3302	46	5100K
	PKWS	T3-60LED-BW	39 watts	1809	46	5100K
		T5-60LED-BW	39 watts	1961	50	5100K
	PKWB	T3-60LED-BW	39 watts	1809	46	5100K
		T5-60LED-BW	39 watts	1961	50	5100K
Providence®	PROL	T3-108LED-BW	124 watts	4941	40	5100K
		T5-108LED-BW	124 watts	4537	37	5100K
	PROV 	T3-60LED-BW	72 watts	3329	46	5100K
		T5-60LED-BW	71 watts	3106	44	5100K
	PROS Type 1	18LED-BW	16 watts	834	52	5100K
	PROS Type 3	27LED-BW	34 watts	1478	44	5100K
	PROS Type 5	36LED-BW	33 watts	1629	49	5100K
	PROB Type 1	18LED-BW	19 watts	1057	56	5100K
	PROB Type 3	27LED-BW	29 watts	1601	55	5100K
	PROB Type 5	36LED-BW	37 watts	2078	56	5100K
	PRSC	36LED-WW	37 watts	1554	42	3500K
		36LED-BW	37 watts	1914	52	5100K
Promenade™	PRMN 	T3-60LED-BW	73 watts	4025	55	5100K
		T5-60LED-BW	72 watts	3855	54	5100K
	PRMS 	T3-60LED-BW	73 watts	4098	56	5100K
		T5-60LED-BW	72 watts	3966	55	5100K
	PRMD 	T3-60LED-BW	73 watts	4389	60	5100K
		T5-60LED-BW	72 watts	4264	59	5100K
Flex™/mini Flex	FH 	T3-99LED-BW	109 watts	5067	47	5100K
		T5-99LED-BW	114 watts	5042	44	5100K
	FM	30LED-WW	32 watts	1124	35	3500K
		30LED-BW	32 watts	1356	42	5100K
Largent™	SLVT 	T3-60LED-BW	73 watts	3018	42	5100K
		T5-60LED-BW	71 watts	2953	42	5100K
Universe® Collection	UCM 	T3-60LED-BW	72 watts	3486	48	5100K
		T5-60LED-BW	70 watts	3207	46	5100K
	UCL 	T3-120LED-BW	138 watts	6221	45	5100K
		T5-120LED-BW	138 watts	6213	45	5100K
	UCS-FCO-ANG	12LED-BW	32 watts	1086	34	5100K
	UCS-ANG	12LED-BW	33 watts	703	21	5100K
	UCB-FLR	12LED-BW	33 watts	703	21	5100K
Cubic Indirect™	INDC	30LED-BW	37 watts	1018	28	5100K
Indirect™	INDA	30LED-BW	33 watts	1162	35	5100K
	INDF	30LED-BW	34 watts	1283	38	5100K
eSconce®/mini eSconce	ES3 Up or down light	36LED-WW	37 watts	1406	38	3500K
		36LED-BW	37 watts	1765	48	5100K
	ES3 Up and down light	54LED-WWX	37/18 watts	1825	33	3500K
		54LED-BWX	37/18 watts	2284	42	5100K
	ME	3LED-BW	5 watts	160	32	5100K

* Other color temperatures and/or configurations available. Please visit www.aal.net for more information.

LED Product Offerings (Cont.)

FAMILY	LUMINAIRE CODE*	LED CONFIGURATION*	WATTAGE CONSUMPTION	LUMEN OUTPUT	LPW	CCT
Oculus®	ON	18LED-WW	22 watts	876	40	3500K
		18LED-BW	21 watts	1342	64	5100K
	OS	30LED-WW	34 watts	1340	39	3500K
		30LED-BW	35 watts	1700	49	5100K
Contemporary Concrete Bollards	CB9S-CO	27LED-WW	33 watts	755	23	3500K
		27LED-BW	33 watts	840	25	5100K
	CB9R-CO	27LED-WW	27 watts	576	21	3500K
		27LED-BW	28.5 watts	735	26	5100K
	CB12R-VERT	36LED-WW	42 watts	1207	29	3500K
		36LED-BW	42 watts	1557	37	5100K
	CB12R-CO	36LED-WW	38 watts	663	17	3500K
		36LED-BW	36 watts	802	22	5100K
	CB16S-VERT	54LED-WW	57 watts	1516	27	3500K
		54LED-BW	56 watts	1604	29	5100K
	CB18R-CO	72LED-BW	72 watts	1072	15	5100K
	CB18R-VERT	72LED-WW	75 watts	2117	28	3500K
Traditional Concrete Bollards	TRD-VR	36LED-BW	37 watts	776	21	5100K
	TSQ-VR	36LED-BW	43 watts	816	19	5100K
Steplights	ASL7-RD	3LED-BW	5 watts	159	32	5100K
	ASL7-SQ	3LED-BW	5 watts	159	32	5100K

* Other color temperatures and/or configurations available. Please visit www.aal.net for more information.



Architectural Area Lighting
 16555 East Gale Ave. | City of Industry | CA 91745
 T 626.968.5666 | F 626.369.2695 | www.aal.net

