



AAL LED Product Offerings



Family	Luminaire Code	LED Configuration	Wattage Consumption	Lumen Output	CCT	
Cubic Indirect™	INDC	30LED-WW	37 watts	686-718	3500K	
		30LED-BW	37 watts	986-1018	5100K	
Indirect™	INDA (Adjustable)	30LED-WW	33 watts	958-965	3500K	
		30LED-BW	33 watts	1154-1162	5100K	
	INDF (Fixed)	30LED-WW	33 watts	881-906	3500K	
		30LED-BW	33 watts	1061-1132	5100K	
eSconce® (Up or down light)	ES3	36LED-WW	37 watts	1406	3500K	
		36LED-BW	37 watts	1765	5100K	
eSconce® (Up and down light)		54LED-WWX	37/18 watts	1825	3500K	
		54LED-BWX	37/18 watts	2284	5100K	
mini eSconce™	ME	LED	5 watts	150	WHT/BL/GRN/RD/AMBR	
miniFlex	FM	30LED-WW	32 watts	1124	3500K	
		30LED-BW	32 watts	1356	5100K	
Oculus® Nano	ON	18LED-WW	18.5 watts	1232	3500K	
		18LED-BW	18.5 watts	1412	5100K	
Oculus® Small	OS	30LED-WW	31 watts	2185	3500K	
		30LED-BW	31 watts	2365	5100K	
Providence® Small (Type 1)	PROS-X	18LED-WW	16.4 watts	675	3500K	
		18LED-BW	16.4 watts	834	5100K	
Providence® Small (Type 3)		27LED-WW	33.6 watts	1152	3500K	
		27LED-BW	33.6 watts	1478	5100K	
Providence® Small (Type 5)		36LED-WW	32.7 watts	1312	3500K	
		36LED-BW	32.7 watts	1629	5100K	
Providence® Bollard (Type 1)		PROB	18LED-WW	19 watts	877	3500K
			18LED-BW	19 watts	1057	5100K
Providence® Bollard (Type 3)			27LED-WW	29 watts	1311	3500K
			27LED-BW	29 watts	1601	5100K
Providence® Bollard (Type 5)	36LED-WW		37 watts	1718	3500K	
	36LED-BW		37 watts	2078	5100K	
Providence® Sconce	PRSC		36LED-WW	37 watts	1554	3500K
			36LED-BW	37 watts	1914	5100K
Steplights Small	ASL7-RD	LED	5 watts	150	WHT/BL/GRN/RD/AMBR	
	ASL7-SQ	LED	5 watts	150	WHT/BL/GRN/RD/AMBR	
Steplights Large	ASL10-RD	LED	9 watts	270	WHT/BL/GRN/RD/AMBR	
	ASL10-SQ	LED	9 watts	270	WHT/BL/GRN/RD/AMBR	

Please visit www.aal.net/aal/tbled.html for more information on our LED products

Architectural Area Lighting
 16555 | East Gale Avenue | CA 91745
 T 626.968.5666 | F 626.369.2695 | www.aal.net